



DECLARATION OF PERFORMANCE

N. 710-CPR-26-01

1. Unique identification code of the product-type: **KUBO LIGHT**
2. Intended uses: **General purpose rendering/plastering mortar (GP)**
3. Manufacturer: **IMPA S.p.A. Unipersonale - Via Crevada, 9/E - 31020 San Pietro di Fioletto (TV), Italy**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2016**

Notified bodies: NA

7. Declared performances:

Reaction to fire	A2-s1,d0
Water absorption	W2
Water permeability after weathering cycles	NPD
Water vapor permeability	19
Adhesion	$\geq 0,3 \text{ N/mm}^2$ - FP:B

Adhesion after weathering cycles	NPD
Thermal conductivity λ	0,31 W/mK (tabulated value)
Durability	NPD
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Cristiano Marchesin
General Manager

San Pietro di Fioletto (TV), 27/01/2026

KUBO LIGHT

CE

IMPA S.p.A. Unipersonale

Via Crevada, 9/E

31020 San Pietro di Feletto (TV), Italy

19

710-CPR-26-01

EN 998-1: 2016

KUBO LIGHT

**General purpose rendering/plastering mortar (GP)
for external/internal use**

Reaction to fire: A2-s1,d0

Water absorption: W2

**Water permeability after
weathering cycles:** NPD

Water vapour permeability: 19

Adhesion: $\geq 0,3 \text{ N/mm}^2$ - FP:B

**Adhesion after weathering
cycles:** NPD

Thermal conductivity λ : 0,31 W/mK (tabulated
value)

Durability: NPD

Dangerous substances: See MSDS