1359 STAINED WAX

WAX-EFFECT FINISH WITH UV FILTERS













Advantages

→ Excellent water repellency
→ Wax-effect with UV filters

Description and Use

Wax-effect wood stain resistant to weathering, formulated with specific additives which give optimal water-repellent effect. The film enhances the natural aspect of wood, preserving it from the effect of degrading agents.
STAINED WAX is suitable for the maintenance of indoor and outdoor woodwork such as matchboarding, attics, fixtures, fences, balconies and can be applied on new or previously painted surfaces.
It can be coloured using the ADVANCE HT tinting system.

Substrate preparation

ON NEW OR HIGHLY ABSORBENT TIMBER:
- Carry out a treatment with SIMPLE WOOD code 1442 and then apply two coats of STAINED WAX, slightly sanding between coats to remove the raised wood fibers.

ALREADY PAINT WOOD:
- The whole surface should be roughened and any flaking parts should be removed, then it is possible to proceed with the application of two coats of STAINED WAX.

Surface must be dry, clean, free from oil or grease.

Application

Application method:
- brush
- spray

Product preparation:
Mix to achieve even colour and consistency.
Diluite with ACQUARAGIA (white spirit) code 1602 at 5-10%.

Recoating:
After 14-16 hours.

IMPA S.p.A Unipersonale Via Crevada, 9/E 31020 San Pietro di Feletto (TV), Italy Tel. +39 0438 4548 Fax +39 0438 454915
Società soggetta ad attività di direzione e coordinamento di Fassa S.r.l. - info@impa.it - www.impa.it

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 12 months. Check the product's shelf life by referring to the production batch number shown on the packaging. The batch number is made of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with the current legislation.

Technical features

Colour	see WOOD SOLUTIONS colour card
Binder	alkyd resin
Appearance of the dry film	semi-matt with wax effect
Specific weight *	0.90 kg/l (±0.02)
Viscosity *	50-70 secons ISO-DIN Cup 6
Indicative actual yield	5-6 m²/l per two coats, according to the type of wood, the porosity and the absorption grade
Air drying (20°C - 65% RH)	1 hour. dust-free
	4-5 hours, dry to touch
	24-48 hours, through drying
EU limit values for VOC content (Directive 2004/42/EC)	Cat. A/e. SB: max VOC 400 g/l product VOC < 400 g/l
* May change according to the colour.	
The data are measured at a temperature of 20°C.	

Warnings

- **The product contains synthetic polymer microparticles (SPM).**
- **INSTRUCTIONS TO PREVENT THE RELEASE OF SYNTHETIC POLYMER MICROPARTICLES INTO THE ENVIRONMENT**
- **In accordance with Regulation (EU) 2023/2055, please follow the procedures below to prevent environmental release.**
- During use and application, avoid accidental release of the product onto soil, into drains, or household wastewater. Apply the product only to the surfaces to be treated.
- Any remaining product should be stored by tightly sealing the original container. Dispose of the product/container in accordance with national regulations.
- If you wish to reuse the tools used for application, follow these steps to clean them in an environmentally responsible manner.
- The water, solvents or thinners used for cleaning tools, as well as any product residues, MUST NOT be released into the environment or poured down domestic drains.
- Remove as much product as possible from the tools used.
- Soak the tools in hot water or in solvent for at least a couple of hours, then remove them from the container.
- Allow the water in the bucket to evaporate and let the tools dry. For solvent-based products, close the container. Do not release the product into the environment and do not pour it into drains.
- Deliver the container with any remaining product / wash water / solvent / cleaning thinner to an authorised waste collection centre, in accordance with national regulations.
- Surface and ambient temperature must be above + 5 (41°F) and below 35°C (95°F).
- Wood must have a maximum humidity of 15%.
- High humidity and excessive thickness can considerably delay the hardening of the applied film.
- Product recommended for expert users.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market and the tinting of the product can lead to slight deviations in the declared values, in the colour and in the aesthetic effects obtained. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.tecnica@impa.it.

IMPA S.p.A Unipersonale Via Crevada, 9/E 31020 San Pietro di Feletto (TV), Italy Tel. +39 0438 4548 Fax +39 0438 454915
Società soggetta ad attività di direzione e coordinamento di Fassa S.r.l. - info@impa.it - www.impa.it